

bias & wire

Westernhat
brim
four sheets



Seam allowance 1/2in.



Bonding line Aa

(heavy weight)
one sheets

Bonding line AA

gromm



Bonding line AA

grommet




DRCOS

SITE <http://www.dr-cos.info/>
MAIL info@dr-cos.com
TWITTER <https://twitter.com/dr-cos.com>
FACEBOOK <https://www.facebook.com/drcos.com/>



size
7 1/4
22.8in.



Westernhat
side
interfacing (heavy weight)
one sheets

Bonding line Ba

Bonding line AB

bias &

Bonding line Aa

interfacing(heavy
one sheet
Westernhat
top

DRCOS
SITE <http://www.dr-cos.info/>
MAIL info@dr-cos.com
Twitter <https://twitter.com/dr-cos>
facebook <https://www.facebook.com/dr-cos.com>

DRCOS
SITE <http://www.dr-cos.info/>
MAIL info@dr-cos.com
Twitter <https://twitter.com/dr-cos>
facebook <https://www.facebook.com/dr-cos.com>

Bonding line BA

Westernhat
brim
interfacing(heavy weight)
two sheets

Bonding line Ab

Bonding line BA

interfacing two




Bonding line Ba

DRCOS

SITE <http://www.dr-cos.info/>
 MAIL info@dr-cos.com
 Twitter <https://twitter.com/dr-cos>
 facebook <https://www.facebook.com/drcoscom>

Bonding line Bb



Westernhat
side
two sheets




Bonding line BB

Seam allowance 1/2in.

DRCOS

SITE <http://www.dr-cos.info/>
MAIL info@dr-cos.com
Twitter [@drcos_com](https://twitter.com/@drcos_com)
facebook <https://www.facebook.com/drcoscom>

**Westernhat
Top
two sheets**



Grain Line



How to make

Sorry if I haven't made myself understood (well) in English. You know I'm poor at English.

- 1.iron on the interfacing(heavy weight) to "top" "side" "brim"
- 2."side" is sew up and loop
- 3."top" and "side" sew pieces
- 4."brim" is sew up and loop
- The surface and the back are same.
- 5.two "brims" are sewn up by a dotted line.
- 6.In a "brim", bias (A wire is put in.)
7. "side" "brim" is sewn up.
- 8.grommet is installed in the grommet location.
- 9.to pass a string through a hole.

DRCOS

SITE <http://www.dr-cos.info/>
MAIL info@dr-cos.com
Twitter [@drcos_com](https://twitter.com/@drcos_com)
facebook <https://www.facebook.com/drcoscom>

Seam allowance 1/2in.